



160mm Bottom Entry SS Case Overview

Features

- Suitable for hydraulic oil and gaseous media that do not corrode any copper base alloy
- Available in nominal sizes 63 and 100
- Thread form: BSP (G1/4 and G1/2), NPT (1/4NPT and 1/2NPT)
- Housing made of Stainless Steel (1.4301)
- Sight glass made of Acrylic
- Glycerine filled
- U-bolt or flange mounting kit on request

Pressure Range	Units (secondary units)	Fitting	Fitting Material
0 to 100	kPa	1/2" NPT	Stainless Steel
0 to 160	kPa	1/2" NPT	Stainless Steel
0 to 250	kPa	1/2" NPT	Stainless Steel
0 to 400	kPa	1/2" NPT	Stainless Steel
0 to 600	kPa	1/2" NPT	Stainless Steel
0 to 800	kPa	1/2" NPT	Stainless Steel
0 to 1000	kPa	1/2" NPT	Stainless Steel
0 to 1600	kPa	1/2" NPT	Stainless Steel
0 to 2500	kPa	1/2" NPT	Stainless Steel
0 to 4000	kPa	1/2" NPT	Stainless Steel
0 to 6000	kPa	1/2" NPT	Stainless Steel
0 to 10000	kPa	1/2" NPT	Stainless Steel
0 to 16000	kPa	1/2" NPT	Stainless Steel
0 to 25000	kPa	1/2" NPT	Stainless Steel
0 to 40000	kPa	1/2" NPT	Stainless Steel
0 to 60000	kPa	1/2" NPT	Stainless Steel
-100 to 0	kPa (inHg)	1/2" NPT	Stainless Steel