



ESD Preset Screwdriver **Overview**

Preset Torque Screwdrivers ensure accurate process control by eliminating under and over tightening. These tools are pre-set to a nominated figure and you can be confident the job will be done correctly with no stripped threads or under tightened screws.

Part No.	Model	Square Drive	Imperial	Intl System (SI)	Metric	Weight (g)	Length (mm)	Repeatability	T-Bar
R065710S	Pro 1350 FH O/W	1/4"	22-120 Lbf In	250-1350 cNm	26-137 Kgf.cm	245	140	+/-6%	Y
R065600S	Pro 450 FH	1/4"	4.5-40 Lbf In	50-450 cNm	5-46 Kgf.cm	230	140	+/-6%	Y
R065610S	Pro 450 FH O/W	1/4"	4.5-40 Lbf In	50-450 cNm	5-46 Kgf.cm	245	140	+/-6%	Y
R065510S	Pro 150 FH O/W	1/4"	1.8-13 Lbf In	20-150 cNm	2-15 Kgf.cm	224	132	+/-6%	N
R065500S	Pro 150 FH	1/4"	1.8-13 Lbf In	20-150 cNm	2-15 Kgf.cm	210	132	+/-6%	N
R065410S	Pro 25 FH O/W	1/4"	0.45-2.2 Lbf In	25-50 cNm	3-5 Kgf.cm	224	132	+/-6%	N
R065400S	Pro 25 FH	1/4"	0.45-2.2 Lbf In	25-50 cNm	3-5 Kgf.cm	210	132	+/-6%	N
R065715S	1350 FH O/W	1/4"	22-120 Lbf In	250-1350 cNm	26-138 Kgf.cm	245	140	+/-6%	Y
R065705S	1350 FH	1/4"	22-120 Lbf In	250-1350 cNm	26-138 Kgf.cm	230	140	+/-6%	Y
R065615S	450 FH O/W	1/4"	4.5-40 Lbf In	50-450 cNm	5-46 Kgf.cm	230	140	+/-6%	Y
R065200S	450 H	1/4"	4.5-40 Lbf In	50-450 cNm	5-46 Kgf.cm	198	138	+/-10%	N
R065605S	450 FH	1/4"	4.5-40 Lbf In	50-450 cNm	5-46 Kgf.cm	230	140	+/-6%	Y
R065100S	150 FH	1/4"	1.8-13 Lbf In	20-150 cNm	2-15 Kgf.cm	198	138	+/-10%	N

Part No.	Model	Square Drive	Imperial	Intl System (SI)	Metric	Weight (g)	Length (mm)	Repeatability	T-Bar
R065515S	150 FH O/W	1/4"	1.8-13 Lbf In	20-150 cNm	2-15 Kgf.cm	224	132	+/-6%	N
R065505S	150 FH	1/4"	1.8-13 Lbf In	20-150 cNm	2-15 Kgf.cm	210	132	+/-6%	N
R065415S	25 FH O/W	1/4"	0.45-22 Lbf In	25-50 cNm	3-5 Kgf.cm	224	132	+/-6%	N
R065405S	25 FH	1/4"	0.45-2 Lbf In	25-50 cNm	.52-3 Kgf.cm	210	132	+/-6%	N